

MATERIAL SAFETY DATA SHEET

CONCRETE RESTORATION PRODUCTS
1772-J Ave de Los Arboles #395
Thousand Oaks Ca. 91362
Phone: (855) 846-8277
www.concreterestorationproducts.com

COUNTY OF LOS ANGELES HAZARDOUS MATERIALS DIVISION: (323) 890-4045
CAL-OSHA: (800) 963-9424

Date Prepared: JULY 8, 2013

SECTION 1 PRODUCT IDENTIFICATION

Product Code: Concrete Restoration Products, CRP STAMP
Product Description: Dry Form Acrylic Emulsion mixed with fine particles of sand and common Portland cement.
HMIS: H-0 F-1 R-0 PP-G
CHEMICAL FAMILY: Portland cement

SECTION II PHYSICAL DATA

BOILING POINT: Not applicable as CRP Stamp is a powdered, solid material.
SPECIFIC GRAVITY: 3.15
VAPOR PRESSURE: Not applicable as CRP Stamp is a powdered, solid material.
PERCENTAGE OF VOLATILES BY VOLUME: 0
VAPOR DENSITY: Not applicable as CRP Stamp is a solid, powdered material.
EVAPORATION RATE: Not applicable as CRP Stamp is a solid, powdered material.
SOLUBILITY IN WATER: Slight (0.1 1.0%)
APPEARANCE & ODOR: White or pigmented various colors in solid material form. No odor.

SECTION III FIRE & EXPLOSION HAZARD DATA

FLASH POINT: CRP Stamp cements are non-combustible and non-explosive.
SPECIAL FIREFIGHTING PROCEDURES: None
FLAMMABILITY OR EXPLOSIVE LIMITS: Not applicable
UNUSUAL FIRE & EXPLOSION HAZARDS: None
EXTINGUISHING MEDIA: Not applicable

SECTION IV HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Respirable Dust —5 mg /m³
Total Dust—10mg / mg
30 million particles / ft³
EFFECTS OF OVEREXPOSURE: Acutely wet CRP Stamp, especially as an ingredient in acrylic (unhardened) concrete, can dry the skin and cause alkali burns. Cement dust can irritate the eyes and upper respiratory tract. Chronic exposure to cement dust can cause inflammation of the lining tissue of the interior of the nose and inflammation of the eyes. Hypersensitive individuals may develop allergic dermatitis (skin rash).
EMERGENCY AND FIRST AID PROCEDURES: Irrigate eyes with water, consult physician. Wash exposed skin areas with soap and water.

SECTION V REACTIVITY DATA

STABILITY: Product is stable. Keep dry until use.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None

SECTION VI SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled: Use dry cleanup methods that do not disperse dust into the air.

Waste disposal method: Material can be returned to container for later use if not contaminated, can be disposed of as an industrial waste, or mixed with water and discarded as a concrete product.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: In dusty environments, use of NIOSH approved respirator is recommended.

VENTILATION: Local exhaust can be used as necessary to control airborne dust levels.

SKIN PROTECTION: Use barrier creams, gloves, boots, and clothing to protect skin from prolonged contact with wet cement, especially in wet, polymer modified concrete.

Immediately after working with cement, workers should shower with soap and water. Precautions must be observed because cement burns with little warning (little heat or discomfort is experienced).

EYE PROTECTION: In dusty environments, use of tight fitting goggles is recommended.

SECTION VIII SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: NONE

OTHER PRECAUTIONS: NONE

Do not apply materials when temperature is below 55 degrees F. or when precipitation is imminent.

Keep material stored in dry area. Do not allow contact with moisture prior to use. Product contains cement and could harden and become useless.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.